

Uncontrolled document as of May 12, 2009. Refer to website for up to date specifications.

LIGHTS
9430
 Remote Area
 Lighting System



9430 Remote Area Lighting System

- Up to 15 hours of burntime
- 2000 lumens of brightness
- Maintenance Free LED Array with life expectancy of 50,000 hours
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock

9430 Remote Area Lighting System Configurations

Cat. #	Description
9430	9430 Remote Area Lighting System

9430 Remote Area Lighting System Specifications

LED Type	LED Life	Tested Lumen Value		
High Flux LED	50000 hrs.	1000 (Low) 2000 (High)		
Lamp Heads	Number of LEDs	Beam Spread	Brightness Settings	
1	24	90 degrees	2	
Battery Type	Battery Burn Time	Battery Charging Time	Battery Life	Low Battery Warning
12v Rechargeable, Sealed	15 hrs. (Low) 8 hrs. (High)	7 hrs. from full discharge	2000 cycles	Intermittent Blinking
12 Volt Primary Sockets	12 Volt Auxiliary Sockets	Watts	Voltage	
1	1	24	12	
Head Material	Body Material	Mast Material		
Polycarbonate/ABS	Polycarbonate/ABS	Glass-Reinforced Plastic		
Lens Material	Switch Type Material			
Polycarbonate	Silicone rubber keypad			
Head Length	Head Width	Head Depth		
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)		
Width Closed	Length Closed	Height Closed		
7.87" (20 cm)	15.75" (40 cm)	9.06" (23 cm)		
Mast Height Extended	Cord Length	Weight		