

Uncontrolled document as of May 12, 2009. Refer to website for up to date specifications.

LIGHTS
9460
 Remote Area
 Lighting System



9460 Remote Area Lighting System

Using solid-state mounted LED's coupled with a thermally efficient light engine and our [1510 Pelican Protector™ Case](#), the RALS 9460 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9460 houses two of it's light heads and it's multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.

Comes with convenient low battery warning system and waterproof activation switch.

9460 Remote Area Lighting System Configurations

Cat. #	Description
9460	9460 Remote Area Lighting System



9460 Remote Area Lighting System Specifications

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	2000 (Low) 4000 (High)

Lamp Heads	Number of LEDs	Beam Spread	Brightness Settings
2	48	90 degrees	2

Battery Type	Battery Burn Time	Battery Charging Time	Battery Life	Low Battery Warning
12v Rechargeable, Sealed	14 hrs. (Low) 7 hrs. (High)	9 hrs. from full discharge	2000 cycles	Intermittent Blinking

12 Volt Primary Sockets	12 Volt Auxiliary Sockets	Watts	Voltage
2		48	12

Head Material	Body Material	Mast Material
Polycarbonate/ABS	Polypropylene	Aluminium

Lens Material	Switch Type Material
Polycarbonate	Silicone rubber keypad

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)

Width Closed	Length Closed	Height Closed
22" (55.9 cm)	13.82" (35.1 cm)	9.02" (22.9 cm)

Mast Height Extended	Cord Length	Weight