

Uncontrolled document as of May 12, 2009. Refer to website for up to date specifications.

**LIGHTS**  
**9470**  
 Remote Area  
 Lighting System



**9470 Remote Area Lighting System**

Using solid-state mounted LED's coupled with a thermally efficient light engine and our 1610 Pelican Protector™ Case, the RALS 9470 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9470 houses all four of it's light heads and it's multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.

Comes with convenient low battery warning system and waterproof activation switch.

**9470 Remote Area Lighting System Configurations**

Cat. #	Description
9470	9470 Remote Area Lighting System



**9470 Remote Area Lighting System Specifications**

<b>LED Type</b>	<b>LED Life</b>	<b>Tested Lumen Value</b>		
High Flux LED	50000 hrs.	4000 (Low) 8000 (High)		
<b>Lamp Heads</b>	<b>Number of LEDs</b>	<b>Beam Spread</b>	<b>Brightness Settings</b>	
4	96	90 degrees	2	
<b>Battery Type</b>	<b>Battery Burn Time</b>	<b>Battery Charging Time</b>	<b>Battery Life</b>	<b>Low Battery Warning</b>
12v Rechargeable, Sealed	14 hrs. (Low) 7 hrs. (High)	8 hrs. from full discharge	2000 cycles	Intermittent Blinking
<b>12 Volt Primary Sockets</b>	<b>12 Volt Auxiliary Sockets</b>	<b>Watts</b>	<b>Voltage</b>	
4	1	96	12	
<b>Head Material</b>	<b>Body Material</b>	<b>Mast Material</b>		
Polycarbonate/ABS	Polypropylene	Aluminium		
<b>Lens Material</b>	<b>Switch Type Material</b>			
Polycarbonate	Silicone rubber keypad			
<b>Head Length</b>	<b>Head Width</b>	<b>Head Depth</b>		
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)		
<b>Width Closed</b>	<b>Length Closed</b>	<b>Height Closed</b>		
24.69" (62.7 cm)	19.57" (49.7 cm)	11.93" (30.3 cm)		
<b>Mast Height Extended</b>	<b>Cord Length</b>	<b>Weight</b>		